

ROSE TALBERT

P A I N T S

1100 / 1140 ROOF & BARN ENAMELS

Roof & Barn paints are both made from high quality soya alkyd oil resin to provide a long lasting finish

RECOMMENDED USES: To be used as a finish paint on metal roofs, gutters, and other exterior metal surfaces, as well as previously painted or new wood surfaces.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, rusty, glossy or unsealed surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50⁰ F.

3. RECOMMENDED PRIMERS:

A. Wood: 250 Bondaplex Acrylic Primer, 120 Reinforced Primer

B. Metal: # 76, 78 & 9074-66 Metal Primers

COLOR: Barn Red / Barn Green

5. TECHNICAL DATA:

DRYING TIME: @ 77⁰F @ 50% RH.
3-6 hr. - TO TOUCH
24 hr. - TO RECOAT

FINISH: Semi-Gloss

COVERAGE: 500 SQ. FT. @ 1.58 MIL DFT

VISCOSITY: 71 KU

VEHICLE TYPE: Soy Alkyd Resin

SOLIDS BY VOLUME: 51.77 ± 2.0%

WEIGHT PER GALLON: 11.34 LB. ± 2.0%

FLASH POINT: 110⁰F.

VOC 374 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew. Lightly sand all glossy surfaces will provide an anchor profile for the new paint to adhere.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Mineral spirits if necessary.

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Mineral spirits.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324