ROSE TALBERT
PAINTS

1740 ACRYLIC WATERBORNE DRY FOG SEMI-GLOSS

1740 Acrylic Waterborne Dry Fog is formulated for high speed application and ease of clean-up. Dry fog is designed for economical painting of commercial ceilings & walls, while being able to be swept up without adhering to surfaces after falling a minimum of 8 to 10 feet contingent on the temperature and humidity.

1. RECOMMENDED USES: For interior use on large wall and ceiling areas, beams, girders, trusses, corrugated metal roof decking, etc.

2. LIMITATIONS:

Surface Temperature: Min. 60 Degrees F
Max. 100 Degrees F

The surface should be dry and at least 5 degrees F above the dew point. A relative humidity of 85% is the maximum. All oil, dirt, and other contaminants must be removed. Precautionary measures should be taken to protect machinery and floors under areas to be painted.

3. RECOMMENDED PRIMERS:

A. Steel: # 76, 78, 8900, & 9001 Metal Primers.
B. Aluminum: #76 Metal Primer.
C. Galvanized: 250 Bondaplex Acrylic Primer, 690 Vinyl Emulsion Primer, Clean 5690 Premium Vinyl Emulsion Primer.
D. Wood: 180 Enamel Undercoat
E. Masonry/Drywall: 690 Vinyl Emulsion Primer, Clean 5690 Premium Vinyl Emulsion Primer
F. Concrete Block: 3550 HD Block Filler, Clean 5550 Heavy Duty Vinyl Block Filler Low VOC

4. COLOR: White & Custom Colors

5. TECHNICAL DATA:

DRYING TIME: @ 77^0F @ 50% RH.
10 min. - TO TOUCH
2 hr. - TO RECOAT
FINISH: Semi-Gloss
COVERAGE: 400 SQ. FT. @ 1.04 MIL DFT
VISCOSITY: 101 KU
VEHICLE TYPE: Acrylic
SOLIDS BY VOLUME: 29.32 $\pm$ 2.0%
WEIGHT PER GALLON: 11.54 LB. $\pm$ 2.0%
VOC 88 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew. Lightly sand all glossy surfaces to provide an anchor profile for the new paint to adhere to.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Water if necessary.

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Warm soapy water.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING**.

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803-796-0324