

ROSE TALBERT

P A I N T S

2300 COUNTRY CLASSIC EXTERIOR SOLID ACRYLIC STAIN

2300 Country Classic Solid Wood Stain is a 100% acrylic exterior stain. It provides exceptional color retention, fade resistance and durability to exterior wood.

Formulated with special fungicidal and wood preservatives, 2300 Country Classic Solid Wood Stain gives an opaque uniform finish that resists cracking, peeling, and blistering.

- 1. RECOMMENDED USES:** For use on new or previously stained wood, trim, siding, shingles, doors, and shutters. Can be used over previously painted surfaces.
- 2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For exterior use. Apply only when the atmospheric temperature and surface temperature will remain above 50⁰ F, and not in foggy or rainy weather. Surface must be absolutely dry before applying. Solid stain is not recommended for floors or decks. Not recommended for use on redwood or cedar as natural chemical stain bleeding will occur.

- 3. RECOMMENDED PRIMERS:**
SELF-PRIMING

- 4. COLOR:** 24 Custom Colors

- 5. TECHNICAL DATA:**

DRYING TIME: @ 77⁰F and 50% RH:
1 hr.- TO TOUCH
6 hrs. - TO RECOAT

FINISH: Flat

COVERAGE: Rough Sawn Wood
Approx. 150 sq.ft. per gal.
Smooth surfaces
Approx. 250 sq.ft. per gal.

VISCOSITY: 82 KU

VEHICLE TYPE: Acrylic

SOLIDS BY VOLUME: 32.01[±] 2.0%

WEIGHT PER GALLON: 10.98 LB.[±] 2.0%

FLASH POINT: N/A

VOC .93 g/l

- 6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.

- 7. MIXING:** One component. Stir thoroughly in a lifting motion before using.

- 8. THINNING:** Do not thin.

- 9. SHELF LIFE:** 12 Months

- 10. CLEAN-UP:** Warm soapy water.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324**