

# ROSE TALBERT

## P A I N T S

### 250 BONDAPLEX INTERIOR/EXTERIOR PRIMER

250 Bondaplex Acrylic Primer is designed to provide excellent stain blocking properties, resistance to nail head rusting, and promotes adhesion to new and repaint surfaces. 250 Bondaplex Primer has excellent adhesion to aged gloss alkyd surfaces, and is both an interior & exterior primer.

**1. RECOMMENDED USES:** To be used as an interior/ exterior primer for wood, trim, doors, shutters, fascia, primed steel, aluminum, galvanized iron, vinyl siding, and masonry surfaces. Recommended for priming aged gloss alkyd surfaces.

**2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, or rusty surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50<sup>0</sup> F, and not in foggy or rainy weather. Avoid using in direct sunlight above 95<sup>0</sup> F.

#### 2. RECOMMENDED FINISHES:

##### Exterior

200 Bondaplex Low Lustre  
1400 Bondaplex Gloss  
1600 Bondaplex Flat  
100 Premium Oil House & Trim  
2600 Weatherbond

##### Interior

300 Prem. Alkyd SG  
400 Prem. Acrylic SG  
860 Imflo Enamel  
8600 WB Acrylic Enamel  
600 & 3500 Flat Latex  
5000 Prem. Latex Flat  
5400 Prem. Acr. Low Lus.  
8400 WB Low Lus. Enam.  
300 Prem. Alkyd SG

**4. COLOR:** White.

#### 5. TECHNICAL DATA:

**DRYING TIME:** @ 77<sup>0</sup>F  
30 min.- TO THE TOUCH  
2 - 4 hr. - TO RECOAT

**FINISH:** Low Lustre

**COVERAGE:** 365 SQ. FT. @ 1.75 MIL DFT

**VISCOSITY:** 95 - 100 KU

**VEHICLE TYPE:** Acrylic

**SOLIDS BY VOLUME:** 39.8 ± 2.0%

**WEIGHT PER GALLON:** 10.84 LB. ± 2.0%

**FLASH POINT:** N/A <sup>0</sup>F.

**VOC** 97 g/l

**6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.

**7. MIXING:** One component. Stir thoroughly in a lifting motion before using.

**8. THINNING:** Water if necessary

**9. SHELF LIFE:** 12 Months

**10. CLEAN-UP:** Warm soapy water.

**11. CAUTION: PROTECT FROM FREEZING:** VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

**FIRST AID:** IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

**NOTE:** ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE TALBERT PAINT COMPANY**  
**P.O. BOX 2658**  
**CAYCE-WEST COLUMBIA, S.C. 29171**  
**803 796-0324**