

ROSE TALBERT

P A I N T S

6030 INSTANT ENAMEL DRY FOG

6030 Instant Enamel Dry Fog is formulated for high speed application and ease of clean-up. Dry fog is designed for economical painting of commercial ceilings & walls, while being able to be swept up without adhering to surfaces after falling a minimum of 8 to 10 feet.

1. RECOMMENDED USES: For interior use on large wall and ceiling areas, beams, girders, trusses, corrugated metal roof decking, etc.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, rusty, glossy or unsealed surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50⁰ F. Not to be used on floors. Extended storage of unused material should be avoided. Precautionary coverage of machinery is advised to protect moving parts.

3. RECOMMENDED PRIMERS:

- A. Steel: # 76, 78, 9072 & 9074-66 Metal Primers.
- B. Aluminum: #76 Metal Primer.
- C. Galvanized: 250 Bondplex Acrylic Primer
690 Vinyl Emulsion Primer, Clean 5690 Premium Vinyl Emulsion Primer.
- D. Wood: 180 Enamel Undercoat

4. COLOR: White

5. TECHNICAL DATA:

DRYING TIME: @ 77⁰F @ 50% RH.
15 min. - TO TOUCH
2-6 hrs. - TO RECOAT

FINISH: Semi-Gloss / Eggshell

COVERAGE: 654 SQ. FT. @ 1.0 MIL DFT

VISCOSITY: 70-75 KU

VEHICLE TYPE: VT Alkyd Resin

SOLIDS BY VOLUME: 40.8 ± 2.0%

WEIGHT PER GALLON: 10.20 LB. ± 2.0%

FLASH POINT: 45 F.

VOC 440 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew. Lightly sand all glossy surfaces to provide an anchor profile for the new paint to adhere to.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Mineral spirits or VM&P Naptha if necessary.

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Mineral spirits.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171**

803-796-0324