

ROSE TALBERT

P A I N T S

8400 WATER BORNE DTM LOW LUSTRE ENAMEL

An extremely durable, water borne DTM modified acrylic enamel, which provides superior adhesion to alkyd gloss and semi-gloss enamel surfaces. For use on most interior surfaces where maximum durability is desired. Also, can be used for select exterior applications.

1. RECOMMENDED USES: Excellent for use over primed, unprimed or previously painted metal including galvanized; primed or previously painted wood, wallboard, plaster, concrete, brick, and concrete block. Use on walls, doors, wood trim, and machinery. Not to be used as a whole house paint on exterior wood.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, or rusty surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50⁰ F, and not in foggy or rainy weather. Avoid using in direct sunlight above 95⁰ F.

3. RECOMMENDED PRIMERS:

- A. Wood: 250 Bondaplex Acrylic Primer or 180 Enamel Undercoat (Alkyd).
- B. Drywall: 690 Vinyl Emulsion Primer, Clean 5690 Premium Vinyl Emulsion Primer, 3590 High Build Primer/Surfacer
- C. Masonry: 690 Vinyl Emulsion Primer, Clean 5690 Premium Vinyl Emulsion Primer
- D. Concrete Block: 3550 HD Block Filler/650 Block Filler, Clean 5550 Heavy Duty Vinyl Block Filler Low VOC
- E. Steel: #76, 78, 9072 & 9074-66 Metal Primers.
- F. Aluminum: #76 Metal Primer & 8900 DTM Primer
- G. Galvanized: 250 Bondaplex or 690 Vinyl Emulsion Primer or 8400 WB Enamel Direct-to-Metal

4. COLOR: White & Custom Colors

5. TECHNICAL DATA:

DRYING TIME: @ 77⁰F, 50% RH.
30 min. - TO THE TOUCH
2-4 hr. - TO RECOAT

FINISH: Low Lustre

COVERAGE: 365 SQ. FT. @ 1.75 MIL DFT

VISCOSITY: 95-100 KU

VEHICLE TYPE: Acrylic

SOLIDS BY VOLUME: 39.8 ± 2.0%

WEIGHT PER GALLON: 10.84 LB. ± 2.0%

FLASH POINT: N/A ⁰F.

VOC 96 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, peeling or flaking paint, oil, mildew and rust.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Water if necessary

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Warm soapy water.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY

P.O. BOX 2658

CAYCE-WEST COLUMBIA, S.C. 29171

803 796-0324