

120 PREMIUM EXTERIOR REINFORCED PRIMER

An exterior primer designed to penetrate and seal new wood surfaces. Dries to a sandable finish and produces excellent enamel hold-out characteristics.

- **1. RECOMMENDED USES:** Use on exterior wood siding, trim clapboard, plywood sash, doors, pre-primed factory siding, and shutters.
- **2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Not to be used as a finish paint.

3. RECOMMENDED FINISHES:

100 Ext. House & Trim, 2000 Ext. House & Trim, 200 Bondaplex, 1400 Bondaplex, 1600 Bondaplex, 2600 Weather Bond, 860 Imflo, 800 Floor & Deck, 750 Floor & Deck.

- 4. **COLOR:** White.
- 5. TECHNICAL DATA:

DRYING TIME: @ 77°F and 50% RH

24 hrs. - TO RECOAT

FINISH: Flat
COVERAGE: 500 SQ. FT. @ 1.94MIL DFT
VISCOSITY: 86 KU
VEHICLE TYPE: Soya Alkyd Resin-Linseed oil
SOLIDS BY VOLUME: 63.14 ± 2.0%
WEIGHT PER GALLON: 12.02 LB. ± 2.0%
FLASH POINT: 115°F
VOC: 284 g/l

- **6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.
- **7. MIXING:** One component. Stir thoroughly in a lifting motion before using.
- 8. THINNING: Mineral spirits if necessary
- 9. SHELF LIFE: 12 Months
- 10. CLEAN-UP: Mineral spirits.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324