

ROSE TALBERT

P A I N T S

1940 SPAR VARNISH

1940 Spar Varnish provides maximum water resistance, protection, and durability where a clear interior / exterior varnish is required. It has a hard, flexible film that flows out to a sparkling gloss finish free of brush marks.

1. RECOMMENDED USES: For new or previously varnished exterior / interior surfaces. Use on boats, decks, exterior trim, lawn furniture, doors, and cabinets. May be used on exterior metal to prevent tarnishing.

2. LIMITATIONS: Do not use over chalk, dust, dirt, grease, mildew, rust, or other improperly prepared surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50°F. Not recommended for textured or rough sawn siding, or floors subject to abuse. Do not use corrosive chemicals on or near this product.

3. RECOMMENDED PRIMERS:

- A. Wood: 1964 Varspeed Sealer
- B. Copper & Brass: Not Required

4. COLOR: Clear

5. TECHNICAL DATA:

DRYING TIME: @ 77°F @ 50% RH
1-2 hr. - TO TOUCH
12 hr. - TO RECOAT

FINISH: Gloss

COVERAGE: 555 SQ. FT. @ 1.0 MIL DFT

VISCOSITY: 80 KU

VEHICLE TYPE: Alkyd Resin

SOLIDS BY VOLUME: 34.61 ± 2.0%

WEIGHT PER GALLON: 7.44 LB. ± 2.0%

FLASH POINT: 98°F

VOC: 513 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew. Lightly sand all glossy surfaces to provide an anchor profile for the finish to adhere to.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Mineral spirits if necessary.

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Mineral spirits.

11. CAUTION: Vapor harmful. May affect brain or nervous system causing dizziness, headache or nausea. Causes nose and throat irritation.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **DO NOT TAKE INTERNALLY.** In case of spillage, absorb and dispose of according to local and federal regulations. **KEEP OUT OF REACH OF CHILDREN.**

KEEP AWAY FROM HEAT AND FLAME. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use (NIOSH/MSHA TC 23C or EQUIVALENT) respirators.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324