

ROSE TALBERT

P A I N T S

290 CLEAR ACRYLIC ALKALI RESISTANT WATERPROOFING PRIMER

290 Clear Acrylic Alkali Resistant Primer is a clear 100% emulsion type surface conditioner. It is designed to allow new above-grade stucco to be coated after a 30 day cure. 290 Primer is designed to consolidate light chalk and dust on the surface to allow a non-penetrating coating to adhere properly. 290 Primer can be used as an interior/ exterior waterproofer when topcoated with an appropriate finish.

1. RECOMMENDED USES: To be used as clear sealer over concrete, stucco, and concrete block. Also, can be used as a joint sealer, and over concrete dust and light chalk.

2. LIMITATIONS: Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Avoid using in direct sunlight above 95°F. 290 Primer is strictly a primer and must be topcoated within 7 days after application. Not to be used as a stand-alone waterproofing system.

3. RECOMMENDED FINISHES:

<u>Exterior</u>	<u>Interior</u>
200 Bondaplex Low Lustre	300 Prem. Alkyd SG
1400 Bondaplex Gloss	400 Prem. Acrylic SG
1600 Bondaplex Flat	600 Prem. Latex Flat
100 Premium Oil House & Trim	860 Imflo Enamel
9600 Weather Barrier Elastomeric	A4400 Acry. Low Lustre
	1300 Acrylic Epoxy
	5000 Prem. Latex Flat
	5400 Prem. Acr. Low Lus.
	8600 WB Gloss Enamel
	8400 WB Low Lus. Enam.

4. COLOR: Clear.

5. TECHNICAL DATA:

DRYING TIME:	@ 77°F
1 hr. minimum - TO RECOAT	
	7 days maximum
FINISH:	Low Sheen
COVERAGE:	200-300 sq. ft./ gallon
VEHICLE TYPE:	Acrylic emulsion
SOLIDS BY WEIGHT:	20.0 ± 2.0%
WEIGHT PER GALLON:	8.53
VOC:	158 g/l

6. SURFACE PREPARATION: Surface must be dry and free of grease, oil, and mildew. Remove loose particles, laitance, & efflorescence by wire brushing or other means. Heavy chalk should be power washed or sand blasted. All new surfaces must cure 7 days.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Water if necessary

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Warm soapy water.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324