

ROSE TALBERT

P A I N T S

3590 HIGH BUILD PRIMER / SURFACER

A heavy bodied , high solids, pigmented interior surfacer filler and sealer especially designed for new dry wall. 3590 High Build Primer/Surfacer sands easily to a smooth finish.

1. RECOMMENDED USES: Use as a filler-sealer surfacer on rough , porous, and uneven drywall. Promotes a smooth even surface for a variety of topcoats. May be mixed with joint compound for thicker high build & texture.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior use only. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Enamel finishes will require 2 Coats for a uniform finish.

3. RECOMMENDED FINISHES:

300 Alkyd Semi-gloss, 400 Acrylic Semi-gloss, 600 Velvet Flat, 860 Imflo Alkyd Gloss, A4400 Acrylic Low-Lustre, 3500 Interior Flat, 4500 Interior Flat, 5500 Professional Flat, 1300 Acrylic Epoxy, 1200 Polyflex Epoxy, 8600 Acrylic Waterborne Enamel Gloss, Clean 5400 Low-Lustre, Clean 5000 Flat, 8400 Low-Lustre.

4. COLOR: White & Colors (up to 2 oz. Per gal.)

5. TECHNICAL DATA:

DRYING TIME: @ 77°F and 50% RH
30 min..- TO TOUCH
4 hr. - TO RECOAT

FINISH: Flat

COVERAGE: 115 SQ. FT. @ 5 MIL DFT

VISCOSITY: 105-115 KU

VEHICLE TYPE: Vinyl Acrylic

SOLIDS BY VOLUME: 35.8

WEIGHT PER GALLON: 12.24 LB. ± 2.0%

FLASH POINT: N/A°F

VOC: 48 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Water if necessary (up to 2 quarts per 5 gallons).

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Warm soapy water.

11. APPLICATION: Can be applied by brush (nylon polyester), roller (3/8" to 3/4"), or airless spray. Use a .017 to a .035 Tip with a 30-40 Mesh Filter for spraying.

12. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324