

7044 ALUMINUM HAMMERTONE ENAMEL

7044 Hammertone Enamel is a high solids, low VOC, and fast drying VT alkyd enamel. It is designed for interior or exterior applications or OEM applications.

1. RECOMMENDED USES: To be used for safety pipe marking, machinery & equipment, railings, fire escapes, racks, steel support structures, conveyors, and fixtures.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, rusty, glossy or unsealed surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50°F.

3. RECOMMENDED PRIMERS:

- 9072,9073 & 9074-66 Metal Primers

- 4. COLOR: Aluminum Hammertone
- 5. TECHNICAL DATA:

DRYING TIME:	@ 77°F @ 50% RH
	15 min TO TOUCH
	2-3 hr TO RECOAT
FINISH:	Gloss
COVERAGE:	664 SQ. FT. @ 1 MIL DFT
VISCOSITY:	65-70 KU
VEHICLE TYPE:	VT alkyd resin
SOLIDS BY VOLUN	ME: $41.4 \pm 2.0\%$
WEIGHT PER GAI	LLON: 7.46 LB. ± 2.0%
FLASH POINT:	45°F
VOC:	454 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew. Hand tool cleaning (SSPC-SP 2) or power tool cleaning (SSPC-SP 3) is preferred.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

- 8. THINNING: Xylene or VM & P Naptha if necessary.
- 9. SHELF LIFE: 12 Months
- 10. CLEAN-UP: Xylene or VM& P Naptha.

11. CAUTION: FLAMMABLE. VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLERASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY P.O. BOX 2658 CAYCE-WEST COLUMBIA, S.C. 29171 (803)796-0324