

ROSE TALBERT

P A I N T S

750 PREMIUM ACRYLIC FLOOR & DECK ENAMEL

Premium Acrylic Floor & Deck Enamel is an easy-to-apply, durable, fast-drying, and low-sheen finish. Acrylic Floor & Deck is alkali and moisture resistant when fully cured.

1. RECOMMENDED USES: To be used as a finish paint for concrete or wood floors, interior/exterior trim, stairs, and properly primed metal.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, or rusty surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Avoid using in direct sunlight above 95°F. Not recommended for tire areas on garage floors. Prolonged soaking of floor with water will affect overall abrasion resistance.

3. RECOMMENDED PRIMERS:

- A. Wood: No Primer Necessary
- B. Steel: # 76, 78, 9072 & 9074-66 Metal Primers.
- C. Aluminum: #76 Metal Primer & 8900 DTM Primer
- D. Galvanized: no primer necessary.
- E. Masonry: 2 Coats Acrylic Floor & Deck

4. COLOR: 4 Ready Mixed

5. TECHNICAL DATA:

DRYING TIME: @ 77°F
1-2 hr.- TO THE TOUCH
12 hr. - TO RECOAT

FINISH: Low Lustre

COVERAGE: 400 SQ. FT. @ 1.36 MIL DFT

VISCOSITY: 73 KU

VEHICLE TYPE: Acrylic

SOLIDS BY VOLUME: 41.45 ± 2.0%

WEIGHT PER GALLON: 10.46 LB. ± 2.0%

FLASH POINT: N/A°F

VOC: 121 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Water if necessary

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Warm soapy water.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324