

ROSE TALBERT

P A I N T S

800 PREMIUM ALKYD FLOOR & DECK ENAMEL

Alkyd Floor & Deck Enamel is formulated to provide a durable interior / exterior finish with excellent underfoot abrasion resistance. A tough, gloss enamel that withstands frequent cleaning with most soaps and detergents.

1. RECOMMENDED USES: To be used as a finish paint for interior / exterior wood, concrete, plaster, and metal. Use to paint trim, floors, stairs, boat decks, machinery, and garage floors.

2. LIMITATIONS: Do not paint over chalk, dust, dirt, grease, mildew, rusty, glossy or unsealed surfaces. Apply only when the atmospheric temperature and surface temperature will remain above 50°F. Avoid using in direct sunlight above 95°F. It is NOT recommended to be used on concrete surfaces which are in direct contact with the ground (without a proper moisture barrier) or on areas that are constantly wet.

3. RECOMMENDED PRIMERS:

- A. Wood: No Primer Necessary
- B. Steel: # 76, 78, 9072 & 9074-66 Metal Primers
- C. Aluminum: # 76 Metal Primer
- D. Galvanized: 250 Bondaplex Acrylic Primer
- E. Concrete Block: 650 Block Filler
- F. Masonry: 2 Coats Floor & Deck Enamel

4. COLOR: 9 Ready Mixed Colors.

5. TECHNICAL DATA:

DRYING TIME: @ 77°F @ 50% RH.
4-6. - TO TOUCH
24 hr. - TO RECOAT

FINISH: High Gloss

COVERAGE: 425 SQ. FT. @ 2 MIL DFT

VISCOSITY: 76 KU

VEHICLE TYPE: Alkyd Resin

SOLIDS BY VOLUME: 49.57 + 2.0%

WEIGHT PER GALLON: 9.98LB. + 2.0%

FLASH POINT: 1100F.

VOC: 392 g/l

6. SURFACE PREPARATION: Surface must be dry and free of chalk, dirt, grease, oil and mildew. Lightly sand all glossy surfaces to provide an anchor profile for the new paint to adhere to.

7. MIXING: One component. Stir thoroughly in a lifting motion before using.

8. THINNING: Mineral spirits if necessary.

9. SHELF LIFE: 12 Months

10. CLEAN-UP: Mineral spirits.

11. CAUTION: PROTECT FROM FREEZING; VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
(803) 796-0324