

## 9079 RED OXIDE PRIMER

9079 Red Oxide Primer is designed to be lead & chromate free. A high solids primer formulated to meet the composition and performance specifications of SSPC-25. Special resins enhance the thru wetting ability of mild surface rust on steel surfaces.

- **1. RECOMMENDED USES:** Use as a shop or field primer for structural or miscellaneous steel.
- **2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior/exterior use. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Not to be recoated with aromatic or other strong solvent paints..
- RECOMMENDED FINISHES: 860 Imflo Alkyd Gloss, 8600 Acrylic Waterborne Enamel Gloss, 7000 Instant Enamel.
- 4. COLOR: Red oxide.
- 5. TECHNICAL DATA:

**DRYING TIME:** @ 77°F and 50% RH

10 hrs. - TO TOUCH 24 hrs. - TO RECOAT

FINISH: Eggshell 1042 SQ. FT. @ 1 MIL DFT **COVERAGE:** VISCOSITY: 74-89 KU **VEHICLE TYPE:** Linseed/Alkyd **SOLIDS BY VOLUME:**  $65.0 \pm 2.0\%$ **WEIGHT PER GALLON:**  $12.0 LB. \pm 2.0\%$ FLASH POINT: 105°F VOC: 268 g/l

- **6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.
- **7. MIXING:** One component. Stir thoroughly in a lifting motion before using.
- 8. THINNING: Mineral spirits if necessary
- **9. SHELF LIFE:** 12 Months
- **10. CLEAN-UP:** Mineral spirits.

11. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171
803 796-0324