

ROSE TALBERT

P A I N T S

TRAFFIC AND ZONE MARKING FLAT LATEX

High quality lead free latex traffic and zone marking paint. Latex marking paints are durable and high-hiding. Recommended for use on asphalt, concrete, and wood. Ideal for painting centerlines and edge-lines of streets, city crosswalks, stop zones, parking lots, warehouse floors, plant maintenance areas, traffic aisles, etc.

1. RECOMMENDED USES:

| | |
|--------------|-------------|
| Centerlines | Crosswalks |
| Parking Lots | Plant Areas |

2. FEATURES/BENEFITS:

- High Hiding
- Excellent Adhesion
- No Tracking after 60 Minutes
- Abrasion Resistant
- Weather Resistant
- Soap & Water Cleanup

3. LIMITATIONS OF USE:

Apply only when air, product and surface temperatures are above 50° F (10° C) and at least 5° F (3° C) above the dew point. Not recommended for immersion service. PROTECT FROM FREEZING. Drying times listed may vary depending on temperature, humidity and air movement.

4. TECHNICAL DATA:

DRYING TIME:

| | |
|---------------|------------|
| To Touch: | 30 Minutes |
| To Handle: | 30 Minutes |
| To Recoat: | 1 Hour |
| To Full Cure: | 4 Hours |

Dry Time @ 77°F (25°C); 50% relative humidity

FINISH: Flat

COVERAGE: 180 SQ. FT. @ 2.5 MIL DFT

VISCOSITY: 90-95 KU

VEHICLE TYPE: Vinyl/Acrylic Resin

SOLIDS BY VOLUME: 27.74±2.0%

WEIGHT PER GALLON: 11.16 LB.±2.0%

VOC: 30 g/l

5. SURFACE PREPARATION: NEW ASPHALT: All new asphalt surfaces should be properly cured before striping. Most asphalt surfaces require a minimum of two weeks curing; however, this may vary on the blend of asphalt to aggregate. Improperly blended or cured asphalt will not withstand the stress exerted by the curing of the paint film and therefore the areas striped may pull the asphalt loose. If there is any doubt regarding this, apply a small stripe of paint to an area and allow to cure and observe the results before striping the entire area. If it is necessary to paint new asphalt surfaces, apply two thin coats 7-8 mils wet each. Allow first coat to thoroughly dry before applying second coat.

NEW CONCRETE: New concrete surfaces should be allowed to cure for at least 28 days before painting. The presence of concrete sealer or efflorescence may interfere with adhesion and can be removed by weathering or mechanical means.

6. APPLICATION: Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat.

Brush: Polyester/Nylon Brush

Roller: 3/8" – 3/4" nap roller cover

7. THINNING: Water if necessary.

8. SHELF LIFE: 12 Months

9. CLEAN-UP: Warm soapy water

10. CAUTION: PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY, DO NOT INDUCE VOMITING.**

NOTE: ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE TALBERT PAINT COMPANY
P.O. BOX 2658
CAYCE-WEST COLUMBIA, S.C. 29171**

803-796-0324