

Page: 1/10

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

#### 1 Identification

· Product identifier

· Trade name: ACRYLIC EPOXY ENAMEL Part B

Product code: 1300 B

· Recommended use and restriction on use

· Recommended use: Coating material

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Rose Talbert Paint Company

901 Frink Street PO BOX 2658

Cayce-West Columbia, SC 29171

Phone: 803.796.0324 Fax: 803.791.0648

Email: info@rosetalbertpaint.com

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

### 2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Lig. 4 H227 Combustible liquid.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS07

· Signal word: Warning

· Hazard statements:

H227 Combustible liquid. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

**Precautionary statements:** 

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing mist, vapors, or spray.

P264 Wash thoroughly after handling.

(Cont'd. on page 2)



Page: 2/10

# **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 1)

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

| · Components: |  |        |
|---------------|--|--------|
| 34590-94-8    | (2-methoxymethylethoxy)propanol  | 60-80% |
|               | Flam. Liq. 4, H227   |        |
|               | Reaction products of Epichlorohydrin and Bisphenol A                   | 5-15%  |
|               | ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1A, H317        |        |
| 112-34-5      | 2-(2-butoxyethoxy)ethanol  | <5%    |
|               | ♦ Eye Irrit. 2A, H319  |        |
| 57-55-6       | propylene glycol   | <5%    |
| 127087-87-0   | Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched | <1%    |
|               | Eye Dam. 1, H318<br>the Acute Tox. 4, H302; Skin Irrit. 2, H315        |        |
|               | ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315                              |        |

#### Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

#### 4 First-aid measures

#### Description of first aid measures

#### · After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

#### · After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

#### After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Cont'd. on page 3)



Page: 3/10

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 2)

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Most important symptoms and effects, both acute and delayed:

Allergic reactions

Dizziness

Irritant to skin and mucous membranes.

Causes eye irritation.

Indication of any immediate medical attention and special treatment needed:

Treat skin and mucous membrane with antihistamine and corticoid preparations.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Water fog / haze

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water stream.
- Special hazards arising from the substance or mixture

Combustible liquid.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Use personal protective equipment as required.

Ensure adequate ventilation.

Keep away from ignition sources.

- Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Absorb liquid components with non-combustible liquid-binding material.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Cont'd. on page 4)



Page: 4/10

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 3)

## 7 Handling and storage

- ·Handling
- Precautions for safe handling:

Keep out of reach of children.

Avoid contact with the eyes and skin.

Use only in well ventilated areas.

Open and handle receptacle with care.

Avoid breathing mist, vapors, or spray.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

## 8 Exposure controls/personal protection

· Control parameters

| Components with limit values that require monitoring at the workplace: |   |                 |  |  |
|--|---|-----------------|--|--|
| 34590-94-8 (2-methoxymethylethoxy)propanol                             |   |                 |  |  |
| PEL (USA)  | Long-term value: 600 mg/m³, 100 ppm<br>Skin   |                 |  |  |
| REL (USA)  | Short-term value: 900 mg/m³, 150 ppm<br>Long-term value: 600 mg/m³, 100 ppm<br>Skin |                 |  |  |
| TLV (USA)  | Short-term value: 909 mg/m³, 150 ppm<br>Long-term value: 606 mg/m³, 100 ppm<br>Skin |                 |  |  |
| EL (Canada)  | Short-term value: 150 ppm<br>Long-term value: 100 ppm<br>Skin                       |                 |  |  |
| EV (Canada)  | Short-term value: 910 mg/m³, 150 ppm<br>Long-term value: 605 mg/m³, 100 ppm         |                 |  |  |
| LMPE (Mexico)  | Short-term value: 150 ppm<br>Long-term value: 100 ppm<br>PIEL                       |                 |  |  |
| 112-34-5 2-(2-b  | utoxyethoxy)ethanol   |                 |  |  |
| TLV (USA)  | Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor                 |                 |  |  |
|  |   | (Cont'd. on pag |  |  |



Page: 5/10

# **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 4

| 57-55-6 propylene glycol |  |  |
|--------------------------|--|--|
|                          | Long-term value: 10 mg/m³  |  |
| EV (Canada)              | Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only |  |

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Not required under normal conditions of use.

NIOSH or EU approved dust respirator should be used for operations generating dust.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

### 9 Physical and chemical properties

Information on basic physical and chemical properties

· Appearance:

Form: Liquid

**Color:** According to product specification

Odor: CharacteristicOdor threshold: Not determined.

pH-value: Not determined.
 Melting point/Melting range: Not determined.
 Boiling point/Boiling range: Not determined.

(Cont'd. on page 6)



Page: 6/10

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

|   |  | (Cont'd. of page 5) |
|---|--|---------------------|
| · Flash point:  | ~75 °C (~167 °F)                                     |                     |
| · Flammability (solid, gaseous):                                  | Not applicable.                                      |                     |
| · Auto-ignition temperature:                                      | Not determined.                                      |                     |
| · Decomposition temperature:                                      | Not determined.                                      |                     |
| · Danger of explosion:  | Product does not present an explosion hazard.        |                     |
| · Explosion limits<br>Lower:<br>Upper:<br>· Oxidizing properties: | Not determined.<br>Not determined.<br>Non-oxidizing. |                     |
| · Vapor pressure:   | Not determined.                                      |                     |
| Density: Relative density: Vapor density: Evaporation rate:       | >1<br>Not determined.<br>Not determined.             |                     |
| · Solubility in / Miscibility with Water:                         | Soluble.   |                     |
| · Partition coefficient (n-octanol/water): Not determined.        |  |                     |
| Viscosity Dynamic: Kinematic: VOC content:                        | Not determined.<br>Not determined.<br>225 g/L        |                     |
| Other information   | No relevant information available.                   |                     |

## 10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Combustible liquid.

Reacts with catalysts, oxidizing agents and strong alkali.

· Conditions to avoid

Excessive heat.

Sources of ignition: sparks, open flame, incompatible materials

- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Carbon monoxide and carbon dioxide

Possible in traces: Nitrogen oxides

(Cont'd. on page 7)



Page: 7/10

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

Chlorine compounds

(Cont'd. of page 6)

## 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 7632-00-0 sodium nitrite

Oral LD50 85 mg/kg (rat)

- Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid release to the environment.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Cont'd. on page 8)



Page: 8/10

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 7)

• Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packagings**
- Recommendation: Disposal must be made according to official regulations.

| 14 Transport information                   |  |  |  |  |
|--|--|--|--|--|
| · UN-Number                                |  |  |  |  |
| · DOT, ADR, IMDG, IATA                     | Not regulated.   |  |  |  |
| UN proper shipping name                    |  |  |  |  |
| · DOT, ADR, IMDG, IATA                     | Not regulated.   |  |  |  |
| Transport hazard class(es)                 |  |  |  |  |
| · DOT, ADR, IMDG, IATA                     |  |  |  |  |
| · Class                                    | Not regulated.   |  |  |  |
| · Packing group                            |  |  |  |  |
| · DOT, ADR, IMDG, IATA                     | Not regulated.   |  |  |  |
| · Environmental hazards                    |  |  |  |  |
| · Marine pollutant:                        | No   |  |  |  |
| Special precautions for user               | Not applicable.  |  |  |  |
| Transport in bulk according to Annex II of |  |  |  |  |
| MARPOL73/78 and the IBC Code               | Not applicable.  |  |  |  |
| · Transport/Additional information:        |  |  |  |  |
| · DOT                                      | Classified as combustible under US DOT regulations.<br>Labeling is only required for single packages ≥119 US<br>gal / 450 L. |  |  |  |
|  |  |  |  |  |

(Cont'd. on page 9)



Page: 9/10

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 8)

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

112-34-5 2-(2-butoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- Carcinogenic categories
- EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients are listed.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision May 19, 2017 / -

(Cont'd. on page 10)



Page: 10/10

# **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: ACRYLIC EPOXY ENAMEL Part B

(Cont'd. of page 9)

#### Abbreviations and acronyms:

LDLo: Lowest Lethal Dose Observed

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxique vPvB: very Persistent and very Bioaccumulative

NIOSH: l'Institut national de recherche sur la sécurité et la santé au travail / National Institute for Occupational Safety (États-Unis)

OSHA: Occupational Safety & Health Administration

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

#### Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com