

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

1 Identification

- **Product identifier**
- **Trade name:** FLAT LATEX DRY FOG
- **Product code:**
2540 (White)
2541 (Black)
- **Recommended use and restriction on use**
- **Recommended use:** Coating material
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Rose Talbert Paint Company
901 Frink Street
PO BOX 2658
Cayce-West Columbia, SC 29171
Phone: 803.796.0324
Fax: 803.791.0648
Email: info@rosetalbertpaint.com
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS07

- **Signal word:** Warning
- **Hazard statements:**
H317 May cause an allergic skin reaction.
- **Precautionary statements:**
 - P261 Avoid breathing vapors.
 - P272 Contaminated work clothing must not be allowed out of the workplace.
 - P280 Wear protective gloves/protective clothing/eye protection.
 - P302+P352 If on skin: Wash with plenty of soap and water.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P363 Wash contaminated clothing before reuse.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 1)

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

1317-65-3	limestone	10-35%
92704-41-1	Kaolin, calcined	10-20%
13463-67-7	titanium dioxide	<10%
1333-86-4	carbon black	<2%
61790-53-2	Diatomaceous earth (Silica-Amorphous)	<2%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2A, H319	<1%
14808-60-7	quartz	<1%
127087-87-0	Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched ⚠ Acute Tox. 4, H302; Eye Irrit. 2A, H319	<1%
111-76-2	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	<1%
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 ⚠ Skin Corr. 1B, H314 ⚠ Skin Sens. 1, H317	<0.05%

· **Additional information:**

For the wording of the listed Hazard Statements, refer to section 16.

Non-classification as a carcinogen is based on non-respirable form of product.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Allergic reactions

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 2)

Dizziness

Slight irritant effect on skin and mucous membranes.

Slight irritant effect on eyes.

· **Indication of any immediate medical attention and special treatment needed:**

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Use personal protective equipment as required.

Ensure adequate ventilation.

· **Environmental precautions** Avoid release to the environment.

· **Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Keep out of reach of children.

Avoid contact with the eyes and skin.

Use only in well ventilated areas.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.

· **Information about storage in one common storage facility:**

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 3)

- Store away from foodstuffs.
- Store away from oxidizing agents.
- **Further information about storage conditions:** Do not freeze.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

1317-65-3 limestone

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

92704-41-1 Kaolin, calcined

LMPE (Mexico)	Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³ (j), A4
---------------	--

13463-67-7 titanium dioxide

PEL (USA)	Long-term value: 15* mg/m ³ *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m ³ withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust; **respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m ³ A4

1333-86-4 carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps. A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

61790-53-2 Diatomaceous earth (Silica-Amorphous)

PEL (USA)	20mppcf or 80mg/m ³ /%SiO ₂
-----------	---

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 4)

REL (USA)	Long-term value: 6 mg/m ³ See Pocket Guide App. C
TLV (USA)	TLV withdrawn
EL (Canada)	Long-term value: 4* 1.5** mg/m ³ *total, **respirable
EV (Canada)	Long-term value: 10* 3** mg/m ³ uncalcined; *inhalable; **respirable
LMPE (Mexico)	Long-term value: 10 mg/m ³ (e)

112-34-5 2-(2-butoxyethoxy)ethanol

TLV (USA)	Long-term value: 67.5* mg/m ³ , 10* ppm *Inhalable fraction and vapor
-----------	---

14808-60-7 quartz

REL (USA)	see Quartz listing
REL (USA)	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m ³ *as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m ³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m ³ *respirable fraction
LMPE (Mexico)	Long-term value: 0.025* mg/m ³ A2, *fracción respirable

111-76-2 2-butoxyethanol

REL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm
EV (Canada)	Long-term value: 20 ppm Skin
LMPE (Mexico)	Long-term value: 20 ppm A3, IBE

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

· Exposure controls

· General protective and hygienic measures:

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 5)

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:**

Not required under normal conditions of use.

NIOSH or EU approved dust respirator should be used for operations generating dust.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

· **Form:** Liquid

· **Color:** White

Black

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Melting point/Melting range:** Not determined.

· **Boiling point/Boiling range:** Not determined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits**

· **Lower:** Not determined.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 6)

Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	1.3-1.4
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· VOC content:	30 g/L
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Carbon monoxide and carbon dioxide
Possible in traces:
Toxic metal compounds
Chlorine compounds

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Sensitization possible through skin contact.

· IARC (International Agency for Research on Cancer):		
13463-67-7	titanium dioxide	2B
1333-86-4	carbon black	2B

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 7)

14808-60-7	quartz	1
------------	--------	---

· **NTP (National Toxicology Program):**

14808-60-7	quartz	K
------------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:**

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

· **Reproductive toxicity:** Based on available data, the classification criteria are not met.

· **STOT-single exposure:** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity** No relevant information available.

· **Persistence and degradability** No relevant information available.

· **Bioaccumulative potential:** No relevant information available.

· **Mobility in soil:** No relevant information available.

· **Additional ecological information**

· **General notes:** Avoid release to the environment.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 8)

14 Transport information

- **UN-Number**
· DOT, ADR, IMDG, IATA Not regulated.
- **UN proper shipping name**
· DOT, ADR, IMDG, IATA Not regulated.
- **Transport hazard class(es)**
· DOT, ADR, IMDG, IATA
· Class Not regulated.
- **Packing group**
· DOT, ADR, IMDG, IATA Not regulated.
- **Environmental hazards**
· Marine pollutant: No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Reference to Attapulgate is based on unbound respirable particles and is not generally applicable to product as supplied.

Reference to titanium dioxide is based on unbound respirable particles and is not generally applicable to product as supplied.

13463-67-7 titanium dioxide

1333-86-4 carbon black

14808-60-7 quartz

· **Chemicals known to cause reproductive toxicity for females:**

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 9)

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

· **IARC (International Agency for Research on Cancer):**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7	titanium dioxide	2B
------------	------------------	----

1333-86-4	carbon black	2B
-----------	--------------	----

14808-60-7	quartz	1
------------	--------	---

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

13463-67-7	titanium dioxide	
------------	------------------	--

1333-86-4	carbon black	
-----------	--------------	--

14808-60-7	quartz	
------------	--------	--

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** December 18, 2017 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Fam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 18, 2017

Revision: December 18, 2017

Trade name: FLAT LATEX DRY FOG

(Cont'd. of page 10)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com