

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

### 1 Identification

- **Product identifier**
- **Trade name: PREMIUM ALKYD SEMI-GLOSS**
- **Product code:** 300 (White), 380 (Midtone), 381 (Deep), 382 (Accent), 383 (Neutral)
- **Recommended use and restriction on use**
- **Recommended use:** Coating material
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Rose Talbert Paint Company  
901 Frink Street  
PO BOX 2658  
Cayce-West Columbia, SC 29171  
Phone: 803.796.0324  
Fax: 803.791.0648  
Email: info@rosetalbertpaint.com
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**
- Flam. Liq. 3 H226 Flammable liquid and vapor.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Carc. 2 H351 Suspected of causing cancer.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

#### Label elements

#### GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### Hazard pictograms:



GHS02 GHS07 GHS08

- **Signal word:** Danger
- **Hazard statements:**  
H226 Flammable liquid and vapor.  
H315 Causes skin irritation.

(Cont'd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 1)

- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.

**Precautionary statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection.
- P240 Ground/bond container and receiving equipment.
- P233 Keep container tightly closed.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P405 Store locked up.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards** There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Components:**

64742-47-8	Distillates (petroleum), hydrotreated light	15-35%
	<ul style="list-style-type: none"> <li> Flam. Liq. 3, H226</li> <li> Asp. Tox. 1, H304</li> <li> Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	

(Cont'd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 2)

1317-65-3	limestone	15-30%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ☠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	15-25%
13463-67-7	titanium dioxide	<20%
1332-58-7	Kaolin	<5%
68953-58-2	Dialkyldimethylammonium Bentonite ⚠ Eye Dam. 1, H318	<2%
1330-20-7	xylene ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	<2%
8052-41-3	Stoddard solvent ⚠ Flam. Liq. 3, H226 ☠ STOT RE 1, H372; Asp. Tox. 1, H304	<1%
22464-99-9	2-ethylhexanoic acid, zirconium salt ⚠ Repr. 2, H361	<1%
96-29-7	2-butanone oxime ☠ Carc. 2, H351 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317 Flam. Liq. 4, H227	<1%
27253-31-2	Cobalt Carboxylate ☠ Carc. 2, H351; Repr. 2, H361 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<1%

**Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
 For the wording of the listed Hazard Statements refer to section 16.

### 4 First-aid measures

**Description of first aid measures**

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:**

Immediately remove any clothing soiled by the product.  
 Immediately wash with water and soap and rinse thoroughly.  
 If skin irritation or rash occurs: Get medical advice/attention.

• **After eye contact:**

Remove contact lenses if worn.  
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Do not induce vomiting; immediately call for medical help.

• **Most important symptoms and effects, both acute and delayed:**

Headache  
 Coughing  
 Allergic reactions  
 Dizziness

(Cont'd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 3)

Irritating to eyes and skin.

· **Danger:**

May be harmful if inhaled.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Indication of any immediate medical attention and special treatment needed:**

Contains Cobalt Carboxylate, 2-butanone oxime. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Water fog / haze

Foam

Carbon dioxide

Gaseous extinguishing agents

Fire-extinguishing powder

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information:** Eliminate all ignition sources if safe to do so.

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

(Cont'd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

(Cont'd. of page 4)

### 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
  - Keep out of reach of children.
  - Avoid contact with the eyes and skin.
  - Prevent formation of aerosols.
  - Avoid splashes or spray in enclosed areas.
  - Use only in well ventilated areas.
- **Information about protection against explosions and fires:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Flammable gas-air mixtures may be formed in empty containers/receptacles.
  - Flammable liquid and vapor.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
  - Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
  - Store away from foodstuffs.
  - Store away from oxidizing agents.
- **Further information about storage conditions:**
  - Store in cool, dry conditions in well sealed receptacles.
  - Do not freeze.
- **Specific end use(s)** No relevant information available.

### 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**64742-47-8 Distillates (petroleum), hydrotreated light**

EL (Canada)	Long-term value: 200 mg/m <sup>3</sup> Skin
-------------	--

**1317-65-3 limestone**

PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust ** respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction

**100-41-4 ethylbenzene**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
-----------	--

(Cont'd. on page 6)

**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 5)

REL (USA)	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

**13463-67-7 titanium dioxide**

REL (USA)	Long-term value: 15* mg/m <sup>3</sup> *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup> withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m <sup>3</sup> *total dust; **respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> total dust
LMPE (Mexico)	Long-term value: 10 mg/m <sup>3</sup> A4

**1332-58-7 Kaolin**

REL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 2* mg/m <sup>3</sup> E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 2(D) mg/m <sup>3</sup> respirable
LMPE (Mexico)	Long-term value: 2* mg/m <sup>3</sup> A4, *fracción respirable

**1330-20-7 xylene**

REL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm

(Cont'd. on page 7)

**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 6)

EV (Canada)	Short-term value: 650 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

**8052-41-3 Stoddard solvent**

PEL (USA)	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV (USA)	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
EL (Canada)	Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 525 mg/m <sup>3</sup>
LMPE (Mexico)	Long-term value: 100 ppm

**22464-99-9 2-ethylhexanoic acid, zirconium salt**

PEL (USA)	Long-term value: 5 mg/m <sup>3</sup> as Zr
REL (USA)	Long-term value: 5 mg/m <sup>3</sup> as Zr
TLV (USA)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup> As Zr
EL (Canada)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup> As Zr

**96-29-7 2-butanone oxime**

WEEL (USA)	Long-term value: 10 ppm DSEN
------------	---------------------------------

**Ingredients with biological limit values:**

**100-41-4 ethylbenzene**

BEI (USA)	0,7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

**1330-20-7 xylene**

(Cont'd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 7)

BEI (USA)	1,5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Keep ignition sources away - Do not smoke.

Pregnant women should strictly avoid inhalation or ingestion.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:**

Not required under normal conditions of use.

NIOSH or EU approved dust respirator should be used for operations generating dust.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

· **Form:** Liquid

· **Color:** According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Melting point/Melting range:** Not determined.

(Cont'd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 8)

· <b>Boiling point/Boiling range:</b>	>35 °C (>95 °F)
· <b>Flash point:</b>	~42 °C (~108 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Auto-ignition temperature:</b>	Not determined.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits</b>	
Lower:	Not determined.
Upper:	Not determined.
· <b>Oxidizing properties:</b>	Non-oxidizing.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density:</b>	
Relative density:	1,3
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b>	
Dynamic:	Not determined.
Kinematic at 40 °C (104 °F):	<20,5 mm <sup>2</sup> /s (estimated)
VOC content:	376 g/L
· <b>Other information</b>	No relevant information available.

### 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- **Possibility of hazardous reactions**  
Flammable liquid and vapor.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**  
Carbon monoxide and carbon dioxide  
Hydrocarbons  
Possible in traces:

(Cont'd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

Toxic metal compounds

(Cont'd. of page 9)

### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**64742-47-8 Distillates (petroleum), hydrotreated light**

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

**100-41-4 ethylbenzene**

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

**1330-20-7 xylene**

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

· **Primary irritant effect:**

- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** May cause sensitisation by skin contact.

· **IARC (International Agency for Research on Cancer):**

100-41-4	ethylbenzene	2B
13463-67-7	titanium dioxide	2B
27253-31-2	Cobalt Carboxylate	2B
14808-60-7	quartz	1

· **NTP (National Toxicology Program):**

Present in trace quantities.

14808-60-7	quartz	K
------------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Eye contact.  
Skin contact.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Carc. 2, Repr. 2

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **Carcinogenicity:** Suspected of causing cancer.

- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.

- **STOT-single exposure:** May cause drowsiness or dizziness.

· **STOT-repeated exposure:**

May cause damage to the hearing organs through prolonged or repeated exposure.

(Cont'd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 10)

- **Aspiration hazard:** May be fatal if swallowed and enters airways.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity**  
Toxic to aquatic life with long lasting effects.

#### 100-41-4 ethylbenzene

EC50	1-10 mg/kg (daphnia)
LC50	1-10 mg/l (Green Algae (chlorophyta))
	4,2 mg/l (Oncorhynchus mykiss)

#### 1330-20-7 xylene

LC50	13,4 mg/l (pimephales promelas)
------	---------------------------------

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information**
- **General notes:** Avoid release to the environment.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT** NA1993

(Cont'd. on page 12)

### Safety Data Sheet







acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 11)

· ADR, IMDG, IATA	UN1263
· UN proper shipping name · DOT	COMBUSTIBLE LIQUID, N.O.S (Petroleum distillates, Ethylbenzene)
· ADR, IMDG · IATA	PAINT Paint
· Transport hazard class(es) · DOT	
	
· Class · Label	3 Combustible liquids 3
· ADR	
 	
· Class · Label	3 (F1) Flammable liquids 3
· IMDG	
 	
· Class · Label	3 Flammable liquids 3
· IATA	
	
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards · Marine pollutant:	Product contains environmentally hazardous substances: Petroleum Distillates Yes Symbol (fish and tree)
· Special precautions for user · Danger code (Kemler):	Warning: Flammable liquids 30

(Cont'd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 12)

· **EMS Number:** F-E,S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT** Classified as combustible under US DOT regulations. Labeling is only required for single packages  $\geq$ 119 US gal / 450 L.

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 10 L each.

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 10 L each.

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

100-41-4 ethylbenzene

1330-20-7 xylene

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

(Cont'd. on page 14)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 13)

13463-67-7	titanium dioxide
14808-60-7	quartz

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

100-41-4	ethylbenzene	D
1330-20-7	xylene	I

· **IARC (International Agency for Research on Cancer):**

100-41-4	ethylbenzene	2B
13463-67-7	titanium dioxide	2B
27253-31-2	Cobalt Carboxylate	2B
14808-60-7	quartz	1

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

13463-67-7	titanium dioxide
14808-60-7	quartz

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** February 28, 2017 / -

· **Abbreviations and acronyms:**

- LDLo: Lowest Lethal Dose Observed
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Flam. Liq. 4: Flammable liquids – Category 4
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Cont'd. on page 15)

**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: February 28, 2017

Revision: February 28, 2017

**Trade name: PREMIUM ALKYD SEMI-GLOSS**

(Cont'd. of page 14)

Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
Carc. 2: Carcinogenicity – Category 2  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1

**Sources**

Website, European Chemicals Agency (echa.europa.eu)  
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)  
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)  
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6  
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.  
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:  
ChemTel Inc.  
1305 North Florida Avenue  
Tampa, Florida USA 33602-2902  
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573  
Website: www.chemtelinc.com