

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

1 Identification Product identifier Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL · Product code: 860 (White), 880 (Midtone), 881 (Deep), 882 (Accent), 883 (Neutral) · Other means of identification: IMFLO Alkyd Gloss Industrial Enamel · Recommended use and restriction on use · Recommended use: Coating material · Restrictions on use: No relevant information available. [•] Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Rose Talbert Paint Company 901 Frink Street PO BOX 2658 Cayce-West Columbia, SC 29171 Phone: 803.796.0324 Fax: 803.791.0648 Email: info@rosetalbertpaint.com **Emergency telephone number:** ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

[•] Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

[·] Label elements

GHS label elements
 The product is classified and labeled according to the Globally Harmonized System (GHS).

 Hazard pictograms:



Signal word: Danger
 Hazard statements:

H226 Flammable liquid and vapor.

(Cont'd. on page 2)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL (Cont'd. of page 1) H315 Causes skin irritation. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H336 May cause drowsiness or dizziness. H373 May cause damage to the hearing organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. **Precautionary statements:** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. P233 Ground/bond container and receiving equipment. P240 P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. Take precautionary measures against static discharge. P243 P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 P308+P313 IF exposed or concerned: Get medical advice/attention. P331 Do NOT induce vomiting. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction. Store in a well-ventilated place. Keep cool. P403+P235 P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

64742-47-8 Distillates (petroleum), hydrotreated light	30-45%
🚯 Asp. Tox. 1, H304	
Skin Irrit. 2, H315; STOT SE 3, H336	
Flam. Liq. 4, H227	
(Cont'd	. on page 3)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

	(Cont'	d. of page
100-41-4	ethylbenzene Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	25-35%
13463-67-7	titanium dioxide	<20%
1317-65-3	limestone	<15%
1332-58-7	Kaolin	<5%
1330-20-7	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	<2%
8052-41-3	Stoddard solvent Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304	<1%
22464-99-9	2-ethylhexanoic acid, zirconium salt	<1%
96-29-7	2-butanone oxime Carc. 2, H351 Eye Dam. 1, H318 Acute Tox. 4, H312; Skin Sens. 1, H317 Flam. Liq. 4, H227	<1%
27253-31-2	Cobalt carboxylate Carc. 2, H351; Repr. 2, H361 Acute Tox. 4, H302; Skin Sens. 1, H317	<1%
100-41-4	ethylbenzene Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Eye Irrit. 2B, H320	<1%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

[•] Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Headache

(Cont'd. on page 4)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 3)

Coughing Allergic reactions Dizziness Irritant to skin and mucous membranes. Slight irritant effect on eyes. **Danger:** May be harmful if inhaled. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways. May cause damage to the hearing organs through prolonged or repeated exposure. **Indication of any immediate medical attention and special treatment needed:** Contains Cobalt carboxylate, 2-butanone oxime. May produce an allergic reaction. Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents: Water fog / haze Foam
Carbon dioxide
Gaseous extinguishing agents
Fire-extinguishing powder
For safety reasons unsuitable extinguishing agents: Water stream.
Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information: Eliminate all ignition sources if safe to do so.

6 Accidental release measures

(Cont'd. on page 5)

Page: 4/15



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 4)

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling

· Precautions for safe handling:

Keep out of reach of children.

Avoid contact with the eyes and skin.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

Flammable liquid and vapor.

[•] Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

• Information about storage in one common storage facility: Store away from foodstuffs.

Store away from oxidizing agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Do not freeze.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

Control parameters

· Components with limit values that require monitoring at the workplace:

64742-47-8 Distillates (petroleum), hydrotreated light		
EL (Canada)	Long-term value: 200 mg/m ³	
	Skin	
100-41-4 ethylbenzene		
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm	
REL (USA)	Short-term value: 545 mg/m ³ , 125 ppm	
	Long-term value: 435 mg/m³, 100 ppm	
	(Cont'd. on page 6)	



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

		(Cont'd. of page 5)	
TLV (USA)	Long-term value: 87 mg/m ³ , 20 ppm BEI		
EL (Canada)	Long-term value: 20 ppm IARC 2B		
EV (Canada)	Short-term value: 540 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm		
LMPE (Mexico)	LMPE (Mexico) Long-term value: 20 ppm		
13463-67-7 tita	nium dioxide		
PEL (USA)	Long-term value: 15* mg/m ³ *total dust		
REL (USA)	See Pocket Guide App. A		
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC		
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B		
EV (Canada)	Long-term value: 10 mg/m ³ total dust		
LMPE (Mexico)	Long-term value: 10 mg/m³ A4		
1317-65-3 limes	stone		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust ** respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
1332-58-7 Kaol	in		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	Long-term value: 2* mg/m³ E; as respirable fraction		
EL (Canada)	Long-term value: 2 mg/m ³		
EV (Canada)	Long-term value: 2(D) mg/m ³ respirable		
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable		
1330-20-7 xyler	1330-20-7 xylene		
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm		
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm		
TLV (USA)	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI		
	1	(Cont'd. on page 7)	



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

	(Cont'd. of page 6)		
EL (Canada)	Short-term value: 150 ppm		
	Long-term value: 100 ppm		
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm		
	Long-term value: 435 mg/m ³ , 100 ppm		
LMPE (Mexico)			
	Long-term value: 100 ppm A4, IBE		
8052-41-3 Stod			
PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm		
REL (USA)	Long-term value: 350 mg/m ³		
	Ceiling limit value: 1800* mg/m ³		
	*15-min		
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm		
EL (Canada)	Short-term value: 580 mg/m ³		
	Long-term value: 290 mg/m ³		
EV (Canada)	Long-term value: 525 mg/m ³		
LMPE (Mexico)	Long-term value: 100 ppm		
22464-99-9 2-et	thylhexanoic acid, zirconium salt		
PEL (USA)	Long-term value: 5 mg/m ³ as Zr		
REL (USA)	Long-term value: 5 mg/m ³ as Zr		
TLV (USA)	Short-term value: 10 mg/m ³		
	Long-term value: 5 mg/m ³ As Zr		
EL (Canada)	Short-term value: 10 mg/m ³		
	Long-term value: 5 mg/m ³		
	As Zr		
96-29-7 2-butar			
WEEL (USA)	Long-term value: 10 ppm		
	DSEN		
-	th biological limit values:		
	100-41-4 ethylbenzene		
BEI (USA) 0.7	g/g creatinine		
	lium: urine		
	e: end of shift at end of workweek ameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)		
	lium: end-exhaled air		
Time: not critical			
	ameter: Ethyl benzene (semi-quantitative)		
	(Cont'd. on page 8)		



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 7)

1330-20-7 xylene BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids • Exposure controls · Personal protective equipment: General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Keep ignition sources away - Do not smoke. Pregnant women should strictly avoid inhalation or ingestion. · Engineering controls: Provide adequate ventilation. · Breathing equipment: Not required under normal conditions of use. NIOSH or EU approved dust respirator should be used for operations generating dust. Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eve protection: Safety glasses · Body protection: Protective work clothing · Limitation and supervision of exposure into the environment No relevant information available. 0 Dhusiaal and shamiaal meansuit

Information on basic physical Appearance:	and chemical properties	
Form:	Liquid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

	(Cont'd. of page
Boiling point/Boiling range:	>35 °C (>95 °F)
Flash point:	~40 °C (~104 °F)
Flammability (solid, gaseous):	Not applicable.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
Oxidizing properties:	Non-oxidizing.
Vapor pressure:	Not determined.
Density:	
Relative density:	1.1-1.2
Vapor density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity	
Dynamic:	Not determined.
Kinematic at 40 °C (104 °F):	<20.5 mm ² /s (estimated)
VOC content:	439 g/L
Other information	No relevant information available.

10 Stability and reactivity

• **Reactivity:** No relevant information available.

• Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Possibility of hazardous reactions

Flammable liquid and vapor.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

· Conditions to avoid Keep ignition sources away - Do not smoke.

Incompatible materials Oxidizers

[•] Hazardous decomposition products

Carbon monoxide and carbon dioxide

Hydrocarbons

Possible in traces:

(Cont'd. on page 10)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 9)

Toxic metal compounds

11 Toxicological information

 Information on toxicological effect 	S
Aguta taxiaitu	

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-47-8 Distillates (petroleum), hydrotreated light

Oral LD50 > 5000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rabbit)

100-41-4 ethylbenzene

Oral LD50 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rabbit)

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

Primary irritant effect:

• On the skin: Based on available data, the classification criteria are not met.

• On the eye: Based on available data, the classification criteria are not met.

· Sensitization: May cause sensitisation by skin contact.

· IARC (International Agency for Research on Cancer):

100-41-4	ethylbenzene	2B
13463-67-7	titanium dioxide	2B
14808-60-7	quartz	1

NTP (National Toxicology Program):

Present in trace quantities.

14808-60-7 quartz

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

• Germ cell mutagenicity: Based on available data, the classification criteria are not met.

· Carcinogenicity: Suspected of causing cancer.

• Reproductive toxicity: Suspected of damaging fertility or the unborn child.

• STOT-single exposure: Based on available data, the classification criteria are not met.

· STOT-repeated exposure:

May cause damage to the hearing organs through prolonged or repeated exposure.

• Aspiration hazard: May be fatal if swallowed and enters airways.

(Cont'd. on page 11)

K



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 10)

2 Ecol	ogical information
	ity
	ic toxicity
	to aquatic life with long lasting effects.
	1-4 ethylbenzene
EC50	1-10 mg/kg (daphnia)
LC50	1-10 mg/l (Green Algae (chlorophyta))
	4.2 mg/l (Oncorhynchus mykiss)
1330-2	20-7 xylene
	13.4 mg/l (pimephales promelas)
· Addit · Gener · Resu · PBT: · vPvB:	 rk: Due to mechanical actions of the product (e.g. agglutinations), damages may occur. cional ecological information ral notes: Avoid release to the environment. Its of PBT and vPvB assessment Not applicable. Not applicable. r adverse effects No relevant information available.
3 Disp	osal considerations
• Recor Can b dispos The u compl	e treatment methods mmendation: be disposed of with household garbage after solidification following consultation with the was sal facility operator and the pertinent authorities and adhering to the necessary technical regulations ser of this material has the responsibility to dispose of unused material, residues and containers iance with all relevant local, state and federal laws and regulations regarding treatment, storage ar

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number		
·DOT	NA1993	
· ADR, IMDG, IATA	UN1263	
		(Cont'd. on page 12)

disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL (Cont'd. of page 11) · UN proper shipping name · DOT COMBUSTIBLE LIQUID, N.O.S (Petroleum distillates, Ethylbenzene) · ADR, IMDG PAINT ·IATA Paint Transport hazard class(es) · DOT 3 Combustible liquids · Class · Label 3 · ADR · Class 3 (F1) Flammable liquids · Label 3 · IMDG · Class 3 Flammable liquids · Label 3 ·IATA · Class 3 Flammable liquids · Label 3 [•] Packing group · DOT, ADR, IMDG, IATA Ш · Environmental hazards Product contains environmentally hazardous substances: Petroleum Distillates · Marine pollutant: Yes Symbol (fish and tree) Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 30 (Cont'd. on page 13)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 12) · EMS Number: F-E,S-E [•] Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. [•] Transport/Additional information: · DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US gal / 450 L. Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c)) Marine pollutants packaged in single or combination · ADR packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.8.1) Limited Quantity for packages less than 30 kg gross and inner packagings less than 10 L each. · IMDG Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7) Limited Quantity for packages less than 30 kg gross and inner packagings less than 10 L each. IATA Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

(Cont'd. on page 14)



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 13)

15 Regulatory information	
 Safety, health and environmental regulations/legisla mixture United States (USA) SARA 	ation specific for the substance or
· Section 302 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
100-41-4 ethylbenzene	
1330-20-7 xylene	
· TSCA (Toxic Substances Control Act)	
All ingredients are listed.	
 Chemicals known to cause cancer: Reference to titanium dioxide is based on unbound respirable product as supplied. Reference to Crystalline Silica and/or Quartz is based on unbou applicable to product as supplied. 	
100-41-4 ethylbenzene	
13463-67-7 titanium dioxide	
14808-60-7 quartz	
· Chemicals known to cause reproductive toxicity for females	S:
None of the ingredients are listed.	
• Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· Carcinogenic categories	
• EPA (Environmental Protection Agency):	
100-41-4 ethylbenzene	D
1330-20-7 xylene	
· IARC (International Agency for Research on Cancer):	
100-41-4 ethylbenzene	2B
13463-67-7 titanium dioxide	2B
27253-31-2 Cobalt carboxylate	28
14808-60-7 quartz	1
· NIOSH-Ca (National Institute for Occupational Safety and He	ealth):
13463-67-7 titanium dioxide	
	(Cont'd. on page 1



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 18, 2017

14808-60-7 quartz

Revision: May 18, 2017

Trade name: IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL

(Cont'd. of page 14)

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision May 18, 2017 / -

· Abbreviations and acronyms:

LDLo: Lowest Lethal Dose Observed ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxique vPvB: very Persistent and very Bioaccumulative NIOSH: l'Institut national de recherche sur la sécurité et la santé au travail / National Institute for Occupational Safety (États-Unis) OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets. Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com