

### Page: 1/10

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

#### 1 Identification

· Product identifier

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

Product code: 8600SG (White)

· Recommended use and restriction on use

· Recommended use: Coating material

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Rose Talbert Paint Company

901 Frink Street PO BOX 2658

Cayce-West Columbia, SC 29171

Phone: 803.796.0324 Fax: 803.791.0648

Email: info@rosetalbertpaint.com

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

### 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.
- · Other hazards There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components	:	
13463-67-7	titanium dioxide	10-20%
1332-58-7	Kaolin	<5%
	ethylene glycol	<2%
	STOT RE 2, H373 Acute Tox. 4, H302	
1317-65-3	limestone	<2%
	(Cont'd	on page 2)



## Page: 2/10

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

### Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

		(Cont'd. of page 1)
112-	34-5 2-(2-butoxyethoxy)ethanol	<1%
127087-	Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched	<1%
	Eye Dam. 1, H318	
	Acute Tox. 4, H302; Skin Irrit. 2, H315	

#### · Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for titanium dioxide note that the substance must be respirable.

#### 4 First-aid measures

- Description of first aid measures
- · After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Most important symptoms and effects, both acute and delayed:

Dizziness

Slight irritant effect on skin and mucous membranes.

Slight irritant effect on eyes.

· Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

### 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: Water stream.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Cont'd. on page 3)



Page: 3/10

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

(Cont'd. of page 2)

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Use personal protective equipment as required.

Ensure adequate ventilation.

- Environmental precautions Avoid release to the environment.
- Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Keep out of reach of children.

Avoid contact with the eyes and skin.

Use only in well ventilated areas.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

- Further information about storage conditions: Do not freeze.
- · Specific end use(s) No relevant information available.

### 8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:			
13463-67-7 titanium dioxide			
PEL (USA)	Long-term value: 15* mg/m³ *total dust		
REL (USA)	See Pocket Guide App. A		
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC		

(Cont'd. on page 4)





# Safety Data Sheet

# acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

		(Cont'd. of page 3)	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B		
EV (Canada)	Long-term value: 10 mg/m³ total dust		
LMPE (Mexico)	Long-term value: 10 mg/m³		
1332-58-7 Kaol	in		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	Long-term value: 2* mg/m³ E; as respirable fraction		
EL (Canada)	Long-term value: 2 mg/m³		
EV (Canada)	Long-term value: 2(D) mg/m³ respirable		
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable		
107-21-1 ethyle	107-21-1 ethylene glycol		
TLV (USA)	Short-term value: NIC-127* NIC-10** mg/m³, NIC-50* ppm Long-term value: NIC-63.5* mg/m³, NIC-25* ppm Ceiling limit value: (100) mg/m³ (H); *inh. fraction + vapor,P:**inh. fraction, H		
EL (Canada)	Short-term value: 20** mg/m³ Long-term value: 10** mg/m³ Ceiling limit value: 100* mg/m³, 50*** ppm *Aerosol; **Particulate; ***Vapour		
EV (Canada)	Ceiling limit value: 100 mg/m³		
LMPE (Mexico)	Ceiling limit value: 100* mg/m³ A4, *solo aerosol		
1317-65-3 limes	stone		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust ** respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
112-34-5 2-(2-b	utoxyethoxy)ethanol		
TLV (USA)	Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor		

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

(Cont'd. on page 5)



Page: 5/10

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

(Cont'd. of page 4)

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Avoid breathing mist, vapors, or spray.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Not required under normal conditions of use.

NIOSH or EU approved dust respirator should be used for operations generating dust.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No relevant information available.

nd chemical properties	
Liquid	
According to product specification	
Characteristic	
Not determined.	
Not applicable.	
Not applicable.	
Not determined.	
Not determined.	
Product does not present an explosion hazard.	
Not determined.	
Not determined.	
	According to product specification Characteristic Not determined.  Not determined. Not determined. Not applicable.  Not applicable.  Not determined.  Product does not present an explosion hazard.

(Cont'd. on page 6)



Page: 6/10

## **Safety Data Sheet**

#### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

		(Cont'd. of page
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	1.2-1.3	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Soluble.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC content:	145 g/L	
Other information	Other information No relevant information available.	

## 10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Carbon monoxide and carbon dioxide

Possible in traces:

Toxic metal compounds

Chlorine compounds

### 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

107-21-1 ethylene glycol

Dermal LD50 9530 mg/kg (rabbit)

- Primary irritant effect:
- On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Sensitization possible through skin contact.

(Cont'd. on page 7)



Page: 7/10

# **Safety Data Sheet**

#### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

(Cont'd. of page 6)

IARC (International Agency for Research on Cancer):

13463-67-7 titanium dioxide

12B

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

### 12 Ecological information

- ·Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid release to the environment.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Cont'd. on page 8)



Page: 8/10

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

(Cont'd. of page 7)

Uncleaned packagings

· Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.
Transport hazard class(es)	
· DOT, ADR, IMDG, IATA · Class	Not regulated.
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.
· Environmental hazards · Marine pollutant:	No
· Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

107-21-1 ethylene glycol

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to Attapulgite is based on unbound respirable particles and is not generally applicable to product as supplied.

(Cont'd. on page 9)



Page: 9/10

## **Safety Data Sheet**

#### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

(Cont'd. of page 8)

Reference to titanium dioxide is based on unbound respirable particles and is not generally applicable to product as supplied.

13463-67-7 titanium dioxide

12174-11-7 Attapulgite (Palygorskite)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

107-21-1 ethylene glycol

· Carcinogenic categories

EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7 titanium dioxide

2B

NIOSH-Ca (National Institute for Occupational Safety and Health):

13463-67-7 titanium dioxide

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision May 19, 2017 / -

#### · Abbreviations and acronyms:

LDLo: Lowest Lethal Dose Observed

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxique

vPvB: very Persistent and very Bioaccumulative

NIOSH: l'Institut national de recherche sur la sécurité et la santé au travail / National Institute for Occupational Safety (États-Unis)

OSHA: Occupational Safety & Health Administration

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/

(Cont'd. on page 10)



Page: 10/10

# **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: May 19, 2017 Revision: May 19, 2017

Trade name: WATER BORNE DTM SEMI-GLOSS ENAMEL

(Cont'd. of page 9)

overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com