

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

1 Identification

- **Product identifier**
- **Trade name: Exterior Oil High Performance**
- **Product code:** 100, 115, 190, 191, 192, 193
- **Recommended use and restriction on use**
- **Recommended use:** Coating material
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Rose Talbert Paint Company
901 Frink Street
PO BOX 2658
Cayce-West Columbia, SC 29171
Phone: 803.796.0324
Fax: 803.791.0648
Email: info@rosetalbertpaint.com
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
- Flam. Liq. 3 H226 Flammable liquid and vapor.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child. Route of exposure: Oral.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 1)

- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H361 Suspected of damaging fertility or the unborn child. Route of exposure: Oral.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.

· Precautionary statements:




- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing mist, vapors, or spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

64742-47-8	Distillates (petroleum), hydrotreated light  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	15-35%
13463-67-7	Titanium dioxide	<20%
1317-65-3	Limestone	<20%
7727-43-7	Barium sulphate, natural	<10%

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 2)

8001-26-1	Linseed oil	<10%
1332-58-7	Kaolin	<10%
1330-20-7	Xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<2%
68953-58-2	Dialkyldimethylammonium Bentonite ⚠ Eye Dam. 1, H318	<2%
1333-86-4	Carbon black	<2%
22464-99-9	2-ethylhexanoic acid, zirconium salt ⚠ Repr. 2, H361	<1%
8052-41-3	Stoddard solvent ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 1, H372; Asp. Tox. 1, H304	<1%
1897-45-6	chlorothalonil (ISO) ⚠ Acute Tox. 2, H330 ⚠ Carc. 2, H351 ⚠ Eye Dam. 1, H318 ⚠ Skin Sens. 1, H317; STOT SE 3, H335	<1%
55406-53-6	3-Iodo-2-propynylbutylcarbamate ⚠ Acute Tox. 3, H331 ⚠ STOT RE 1, H372 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<1%
136-53-8	zinc bis(2-ethylhexanoate) ⚠ Repr. 2, H361 ⚠ Eye Irrit. 2A, H319	<1%
96-29-7	2-butanone oxime ⚠ Carc. 2, H351 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317 Flam. Liq. 4, H227	<1%
100-41-4	Ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332 Eye Irrit. 2B, H320	<1%
67-68-5	dimethyl sulfoxide Flam. Liq. 4, H227	<1%
27253-31-2	Cobalt Carboxylate ⚠ Carc. 2, H351; Repr. 2, H361 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<1%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 3)

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Respiration of particulates is unlikely during normal usage.
Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately remove any clothing soiled by the product.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Headache
Coughing
Allergic reactions
Dizziness
Irritant to skin and mucous membranes.
Causes serious eye irritation.

· **Danger:**

Suspected of causing cancer. Route of exposure: Inhalation.
Suspected of damaging fertility or the unborn child. Route of exposure: Oral.
May be fatal if swallowed and enters airways.
Danger of impaired breathing.

· **Indication of any immediate medical attention and special treatment needed:**

Contains chlorothalonil (ISO), 3-Iodo-2-propynylbutylcarbamate, 2-butanone oxime, Cobalt Carboxylate.
May produce an allergic reaction.
Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Water fog / haze
Foam
Carbon dioxide
Gaseous extinguishing agents
Fire-extinguishing powder

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.
Wear fully protective suit.

· **Additional information:** Eliminate all ignition sources if safe to do so.

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 4)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

- **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up**

Towel or mop up material and collect in a suitable container.

For large spills, absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling**

- **Precautions for safe handling:**

Keep out of reach of children.

Avoid contact with the eyes and skin.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

Flammable liquid and vapor.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

Do not allow product to freeze.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 5)

· Control parameters

· Components with limit values that require monitoring at the workplace:

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada)	Long-term value: 200 mg/m ³ Skin
-------------	--

13463-67-7 Titanium dioxide

PEL (USA)	Long-term value: 15* mg/m ³ *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10* 3** mg/m ³ **total dust; **respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m ³ A4

1317-65-3 Limestone

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

7727-43-7 Barium sulphate, natural

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 5* mg/m ³ *inhalable fraction; E
EL (Canada)	Long-term value: 5 mg/m ³ inhalable
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m ³

8001-26-1 Linseed oil

OEL (Canada)	Short-term value: 10* 3** mg/m ³ *Mist **Respirable mist
TWA (Canada)	Short-term value: 10* 3** mg/m ³ *Mist **Respirable mist

1332-58-7 Kaolin

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 6)

TLV (USA)	Long-term value: 2* mg/m ³ E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m ³
EV (Canada)	Long-term value: 2(D) mg/m ³ respirable
LMPE (Mexico)	Long-term value: 2* mg/m ³ A4, *fracción respirable

1330-20-7 Xylene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

1333-86-4 Carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

22464-99-9 2-ethylhexanoic acid, zirconium salt

PEL (USA)	Long-term value: 5 mg/m ³ as Zr
REL (USA)	Long-term value: 5 mg/m ³ as Zr
TLV (USA)	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ As Zr
EL (Canada)	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ As Zr

8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
-----------	---

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 7)

REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm
EL (Canada)	Short-term value: 580 mg/m ³ Long-term value: 290 mg/m ³
EV (Canada)	Long-term value: 525 mg/m ³
LMPE (Mexico)	Long-term value: 100 ppm

1897-45-6 chlorothalonil (ISO)

EL (Canada) | IARC 2B

96-29-7 2-butanone oxime

WEEL (USA) | Long-term value: 10 ppm
DSEN

100-41-4 Ethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 87 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

67-68-5 dimethyl sulfoxide

WEEL (USA) | Long-term value: 250 ppm

Ingredients with biological limit values:

1330-20-7 Xylene

BEI (USA) | 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 Ethylbenzene

BEI (USA) | 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
Medium: end-exhaled air
Time: not critical
Parameter: Ethyl benzene (semi-quantitative)

Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 8)

- Keep away from foodstuffs, beverages and feed.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Keep ignition sources away - Do not smoke.
- Pregnant women should strictly avoid inhalation or ingestion.

- **Engineering controls:** Provide adequate ventilation.

- **Breathing equipment:**

Not required under normal conditions of use.

NIOSH or EU approved dust respirator should be used for operations generating dust.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No relevant information available.

- **Risk management measures** No relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Liquid

Color: According to product specification

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Melting point/Melting range:** Not determined.

- **Boiling point/Boiling range:** >35 °C (>95 °F)

- **Flash point:** >40 °C (>104 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 9)

- | | |
|---|--------------------------------------|
| · Explosion limits | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Oxidizing properties: | Non-oxidizing. |
| · Vapor pressure: | Not determined. |
| · Density: | |
| Relative density: | Not determined. |
| Vapor density: | Not determined. |
| Evaporation rate: | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity | |
| Dynamic: | Not determined. |
| Kinematic at 40 °C (104 °F): | <20.5 mm ² /s (estimated) |
| · Other information | No relevant information available. |

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- **Possibility of hazardous reactions**
Flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Under fire conditions only:
Carbon monoxide and carbon dioxide
Hydrocarbons
Possible in traces:
Toxic metal compounds

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

64742-47-8 Distillates (petroleum), hydrotreated light

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 10)

Dermal	LD50	>2000 mg/kg (rabbit)
1330-20-7 Xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
55406-53-6 3-Iodo-2-propynylbutylcarbamate		
Oral	LD50	1470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4h	>6.89 mg/l (rat)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Causes eye irritation.
- **Sensitization:** May cause sensitization by skin contact.

· **IARC (International Agency for Research on Cancer):**

13463-67-7	Titanium dioxide	2B
1333-86-4	Carbon black	2B
1897-45-6	chlorothalonil (ISO)	2B
100-41-4	Ethylbenzene	2B
27253-31-2	Cobalt Carboxylate	2B
14808-60-7	Quartz	1

- **NTP (National Toxicology Program):**
Present in trace quantities.

14808-60-7	Quartz	K
------------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer. Route of exposure: Inhalation.
- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child. Route of exposure: Oral.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity**
Toxic to aquatic life with long lasting effects.

1330-20-7 Xylene	
LC50	13.4 mg/l (pimephales promelas)

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.

(Cont'd. on page 12)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance



(Cont'd. of page 11)

- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information**
- **General notes:** Avoid release to the environment.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT · ADR/RID/ADN, IMDG, IATA | <p style="margin-left: 20px;">NA1993</p> <p style="margin-left: 20px;">UN1263</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR/RID/ADN, IMDG · IATA | <p style="margin-left: 20px;">Combustible liquid, n.o.s. (petroleum distillates)</p> <p style="margin-left: 20px;">PAINT</p> <p style="margin-left: 20px;">Paint</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="margin-left: 20px;">  </div> <p style="margin-left: 20px;">3</p> <p style="margin-left: 20px;">3</p> |
| <ul style="list-style-type: none"> · ADR/RID/ADN | <div style="margin-left: 20px;">  </div> <p style="margin-left: 20px;">3 (F1)</p> <p style="margin-left: 20px;">3</p> |

(Cont'd. on page 13)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 12)

· **IMDG, IATA**



· **Class** 3
· **Label** 3

· **Packing group**
· **DOT, ADR/RID/ADN, IMDG, IATA** III

· **Environmental hazards** Product contains environmentally hazardous substances: Petroleum Distillates

· **Marine pollutant:**



Yes

· **Special precautions for user** Warning: Flammable liquids
· **Danger code (Kemler):** 30
· **EMS Number:** F-E,S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT** Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥ 119 US gal / 450 L.
Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR/RID/ADN** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· **IMDG** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine

(Cont'd. on page 14)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 13)

pollutants. (See 2.10.2.7)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

7727-43-7	Barium sulphate, natural
1330-20-7	Xylene

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

13463-67-7	Titanium dioxide
1333-86-4	Carbon black
1897-45-6	chlorothalonil (ISO)
100-41-4	Ethylbenzene
14808-60-7	Quartz

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	Toluene
----------	---------

· **EPA (Environmental Protection Agency):**

7727-43-7	Barium sulphate, natural		D, CBD(inh), NL(oral)
-----------	--------------------------	--	-----------------------

(Cont'd. on page 15)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 14)

1330-20-7	Xylene	I
100-41-4	Ethylbenzene	D
100-41-4	Ethylbenzene	D

· **IARC (International Agency for Research on Cancer):**

13463-67-7	Titanium dioxide	2B
1333-86-4	Carbon black	2B
1897-45-6	chlorothalonil (ISO)	2B
100-41-4	Ethylbenzene	2B
27253-31-2	Cobalt Carboxylate	2B
14808-60-7	Quartz	1

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- OSHA: Occupational Safety & Health Administration
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Flam. Liq. 4: Flammable liquids – Category 4
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 2: Acute toxicity – Category 2
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
- Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

- Website, European Chemicals Agency (echa.europa.eu)
- Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
- Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
- Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
- Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
- Safety Data Sheets, Individual Manufacturers

(Cont'd. on page 16)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 22, 2019

Trade name: Exterior Oil High Performance

(Cont'd. of page 15)

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com