

# ROSE TALBERT

## P A I N T S

### CLEAN 5690 PREMIUM VINYL EMULSION PRIMER ZERO VOC

Clean 5690 Vinyl Emulsion Primer is a sealer especially designed to lay down the nap of drywall. It has excellent enamel hold-out properties that prevent variation of sheen in the finish coats. Clean 5000 Products are zero VOC and low odor formulations.

**1. RECOMMENDED USES:** Use on new sheetrock or drywall. Also may be used on plaster, concrete, brick, wood, or previously painted porous surfaces.

**2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior use only. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather.

**3. RECOMMENDED FINISHES:**

300 Alkyd Semi-gloss, 400 Acrylic Semi-gloss, 600 Velvet Flat, 860 Imflo Alkyd Gloss, A4400 Acrylic Low-Lustre, 3500 Interior Flat, 4500 Interior Flat, 5500 Professional Flat, 1300 Acrylic Epoxy, 1200 Polyflex Epoxy, 8600 Acrylic Waterborne Enamel Gloss, & Clean 5000 Flat, Clean 5400 Low-Lustre, 8400 Low-Lustre.

**4. COLOR:** White.

**5. TECHNICAL DATA:**

**DRYING TIME:** @ 77°F and 50% RH:  
30 min.- TO TOUCH  
2 - 4 hr. - TO RECOAT

**FINISH:** Flat

**COVERAGE:** 329 SQ. FT. @ 1.5 MIL DFT

**VISCOSITY:** 95 - 100 KU

**VEHICLE TYPE:** Vinyl Acrylic

**SOLIDS BY VOLUME:** 30.86 ± 2.0%

**WEIGHT PER GALLON:** 11.08 LB. ± 2.0%

**FLASH POINT:** N/A °F

**VOC:** 0 g/l

**6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.

**7. MIXING:** One component. Stir thoroughly in a lifting motion before using.

**8. THINNING:** Water if necessary

**9. SHELF LIFE:** 12 Months

**10. CLEAN-UP:** Warm soapy water.

**11. CAUTION:** PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

**FIRST AID:** IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

**NOTE:** ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE TALBERT PAINT COMPANY  
P.O. BOX 2658  
CAYCE-WEST COLUMBIA, S.C. 29171  
803 796-0324**