

# ROSE TALBERT

## P A I N T S

### 650 PREMIUM ACRYLIC BLOCK FILLER

A heavy-bodied, high solids, pigmented filler sealer especially designed for porous block surfaces. It is designed for both interior and exterior use.

**1. RECOMMENDED USES:** Use as a filler-sealer on rough, porous concrete block. May be top coated with latex and solvent-thinned opaque paints.

**2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior/exterior use.. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather.

**3. RECOMMENDED FINISHES:**

300 Alkyd Semi-gloss, 400 Acrylic Semi-gloss, 600 Velvet Flat, 860 Imflo Alkyd Gloss, A4400 Acrylic Low-Lustre, 3500 Interior Flat, 4500 Interior Flat, 5500 Professional Flat, 1300 Acrylic Epoxy, 1200 Polyflex Epoxy, 8600 Acrylic WB Enamel Gloss, 200 Bondaplex Low Lustre, 1400 Bondaplex Gloss, 1600 Bondaplex Flat, & 2600 Weather bond, Clean 5000 Premium Vinyl Latex Flat, Clean 5400 Premium Acrylic Low- Lustre Enamel Zero VOC, 8400 Water Borne DTM Low-Lustre Enamel.

**4. COLOR:** White.

**5. TECHNICAL DATA:**

**DRYING TIME:** @ 77°F and 50% RH  
30 min..- TO TOUCH  
8 hr. - TO RECOAT

**FINISH:** Flat

**COVERAGE:** 75 SQ. FT. @ 9.8 MIL DFT

**VISCOSITY:** 124 KU

**VEHICLE TYPE:** Acrylic

**SOLIDS BY VOLUME:** 54.14 ± 2.0%

**WEIGHT PER GALLON:** 13.12 LB. ± 2.0%

**FLASH POINT:** N/A°F

**VOC:** 54 g/l

**6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil and mildew.

**7. MIXING:** One component. Stir thoroughly in a lifting motion before using.

**8. THINNING:** Water if necessary

**9. SHELF LIFE:** 12 Months

**10. CLEAN-UP:** Warm soapy water.

**11. CAUTION:** PROTECT FROM FREEZING: VAPOR MAYBE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE, ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

**FIRST AID:** IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

**NOTE:** ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

**ROSE TALBERT PAINT COMPANY**  
**P.O. BOX 2658**  
**CAYCE-WEST COLUMBIA, S.C. 29171**  
**803 796-0324**