

75 Red Chromate Primer is specially formulated for fast drying and its rust inhibitive properties. The fast drying qualities will speed overall production and handling time.

**1. RECOMMENDED USES:** Use as a primer for interior or exterior metal surfaces such as structural steel, iron, tanks, water towers, fire escapes, doors, etc.

**2. LIMITATIONS:** Do not paint over chalk, dust, dirt, grease, mildew, rusty or glossy surfaces. For interior/ exterior use. Apply only when the atmospheric temperature and surface temperature will remain above 50°F, and not in foggy or rainy weather. Not to be recoated with aromatic or other strong solvent paints.

**3. RECOMMENDED PRIMERS:**

50 Wallkyd Flat Oil, 300 Alkyd Semi-gloss, 400 Acrylic Semi-gloss, 600 Velvet Flat, 860 Imflo Alkyd Gloss, A4400 Acrylic Low-luster, 8600 Acrylic Waterborne Enamel Gloss, 100 Ext. House & Trim, 200 – 1400-1600 Bondaplex Acrylic Paint.

**4. COLOR:** Red

**5. TECHNICAL DATA:**

Drying Time: .....@ 77°F and 50% RH  
30 min.- TO THE TOUCH  
12hr. - TO RECOAT

Finish: ..... Flat

Coverage: ..... 500 SQ. Ft. @ 1.66 MIL DFT

Viscosity: ..... .72 KU

Vehicle Type: ..... Vinyl Toluene Veg. Oil

Solids By Volume: ..... 34.47 + 2.0%

Weight Per Gallon: ..... 9.27 LB + 2.0%

Flash Point: ..... 64°F

VOC: ..... 368 g/l

**6. SURFACE PREPARATION:** Surface must be dry and free of chalk, dirt, grease, oil, and mildew.

**7. MIXING:** One component. Stir thoroughly in a lifting motion before using.

**8. THINNING:** Minerals spirits if necessary.

**9. SHELF LIFE:** 12 Months

**10. CLEAN-UP:** Mineral spirits.

**11. CAUTION:** PROTECT FROM FREEZING: VAPOR MAY BE HARMFUL. BREATHING OF VAPOR MAY CAUSE RESPIRATORY IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. CAUSES EYE IRRITATION. DO NOT TAKE INTERNALLY. IN CASE OF SPILLAGE ABSORB AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS. KEEP OUT OF REACH OF CHILDREN.

**FIRST AID:** IN CASE OF SKIN CONTACT, FLUSH WITH PLENTY OF WATER; FOR EYES, FLUSH WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. IF EFFECTED BY INHALATION, MOVE TO FRESH AIR. **IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.**

**NOTE:** ALL TECHNICAL ADVICE, RECOMMENDATIONS AND SERVICES RENDERED BY THE SELLER IS GRATIS. SELLER ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. ANY INFORMATION CONTAINED HEREIN IS BELIEVED BY THE SELLER TO BE RELIABLE AND INTENDED FOR THE USES BY PERSONS HAVING SKILL AND KNOW-HOW, AT THEIR DISCRETION AND RISK. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND THE MANNER OF USE IS THE SOLE RESPONSIBILITY OF THE USER.

ROSE  
TALBERT  
PAINT COMPANY

P.O. BOX 2658  
CAYCE-WEST COLUMBIA, S.C. 29171  
803-796-0324